

## USB 3.2 Gen 2



## Product Highlights:

- USB 3.2 Gen 2 high-speed interface with data transfer rates up to 10Gbps<sup>1</sup>
- Features a premium aluminum enclosure providing exceptional heat dissipation
- Supports large capacity SSD up to 2TB to store, transfer and play your favorite content
- Features a rugged bumper for added protection on-the-go
- Support PCIe (NVMe) and SATA 6Gbps<sup>1</sup> SSD, and compatible with M key and B&M key with sizes 2230/2242/2260/2280 form factor
- Comes with Type-C to Type-C cable and Type-C to Type-A cable
- Plug & Play design with no additional power or drivers required
- Two-year limited warranty



## Blazing Fast M.2 NVMe SSD Enclosure

The Lexar® E10 M.2 SSD Enclosure supports both M.2 PCIe NVMe and SATA SSD. It also features a high-speed USB 3.2 Gen 2 interface for data transfer rates up to 10Gbps<sup>1</sup>. Designed with a premium aluminum enclosure for added heat dissipation, the enclosure also features a rugged bumper for added durability and portability.

**Move files at USB 3.2 Gen 2 speed.** Designed with a USB 3.2 Gen 2 high-speed interface, the Lexar E10 SSD Enclosure features data transfer rates of up to 10Gb/s<sup>1</sup> for steady and efficient transfer speeds.

**Excellent heat dissipation capability.** Features a premium aluminum enclosure providing exceptional heat dissipation for blazing fast data transfers and keeping your data safe.

**Supports M.2 PCIe NVMe and SATA SSD.** Lexar E10 M.2 SSD enclosure is compatible with 2230, 2242, 2260, and 2280 form factor. It also supports M.2 PCIe NVMe and SATA SSD with a maximum capacity of 2TB with M key / B&M key.

**Rugged as it is durable.** The E10 M.2 SSD Enclosure features a rugged bumper for added protection against drop, shock and vibration.

**Versatile and convenient to use.** The E10 M.2 SSD Enclosure features a quick-draw cable for added accessibility and with its built-in magnetic connector, swapping cables is a breeze. The E10 comes with Type-C to Type-C cable and a USB Type-C to standard USB Type-A cable for added versatility. And, with no additional drivers needed, the E10 Enclosure is plug and play ready for added convenience.

**Rigorously tested.** All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

*For more than 25 years, Lexar has been a trusted leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit [www.lexar.com](http://www.lexar.com).*

<sup>1</sup>Theoretical transfer speeds for the NVMe protocol is up to 10Gbps and up to 6Gbps for the SATA protocol. Speeds are based on internal testing. Actual performance may vary.

## NOTE:

Security safeguards, by their nature, are capable of circumvention. Lexar does not guarantee data will be 100% secure from unauthorized access, alteration, or destruction.

To ensure compatibility and best performance, please visit [lexar.com/downloads](http://lexar.com/downloads) to download the latest USB 3.2 driver.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

Lexar is not liable for any loss of data or images.

[www.lexar.com](http://www.lexar.com)

©2022 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

## USB 3.2 Gen 2

Lexar Retail Sku	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LPAE10N-RNBNG	Global	843367127245	80843367127241	12

## Specifications

Form Factor	SSD Enclosure
Interface	USB 3.2 Gen 2 Type-C
Speed	Features a high-speed USB 3.2 Gen 2 interface for data transfer rates up to 10Gbps <sup>1</sup>
Operating Temperature	0° to 40° C (32°F to 104°F)
Storage Temperature	-25° C to 85° C (-13°F to 185°F)
Shock	1500G, duration 0.5ms, Half Sine Wave
Vibration	7~800Hz, 3.08Grms, 30min/axis(X,Y,Z)
Dimension	120 mm x 49 mm x 13 mm / 4.72" x 1.93" x 0.51"
Weight	77g / 0.17lbs (Only Enclosure)
Warranty	Two-year limited warranty

[www.lexar.com](http://www.lexar.com)

©2022 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.