GeForce RTX™ 4070 Ti SUPER 16G VENTUS 2X OC

SPECIFICATIONS

Modèle	GeForce RTX™ 4070 Ti SUPER 16G VENTUS 2X OC
Processeur graphique	NVIDIA® GeForce RTX™ 4070 Ti SUPER
Cœurs	8448 unités
Mémoire	16 Go GDDR6X
Bus Mémoire	256-bit
Fréquence du GPU	Extreme Performance : 2655 MHz (MSI Center) Boost : 2640 MHz
Vitesse mémoire	21 Gb/s
Nombre d'écrans supportés	4
Technologie G-SYNC™	Oui
Résolution numérique maximum	7680 x 4320
Support du procédé HDCP	Oui
Bloc d'alimentation recommandé	700 W
Connecteurs alimentation	1 x 16 broches
Sorties	3 x DisplayPort (v1.4a) 1 x HDMI™ (Support 4K @ 120 Hz HDR, 8K @ 60 Hz HDR et de la fréquence de rafraîchissement variable telle que spécifiée par la norme HDMI™ 2.1a)
Version OpenGL	4.6
Dimensions	242 x 125 x 51 mm
Poids	882 g / 1214 g

CONNECTIONS

1. DisplayPort
2. HDMI™

FEATURES

Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.

TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.

Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.

Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.

Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.

Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.

Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.

MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.